

GENERAL DATA	
Model	BP19SK
Continuous / Prime power (P.R.P)	14.4
Stand-by power (L.T.P)	16.7
Amps (A)	62.6
Power Factor / Cos (ϕ)	0.8
Frequency	50
Voltage	230
No. phases	Single Phase
Engine Speed	3000

DIMENSIONS (UNPACKED)*	
Length (-L- m)	1560
Width (-W- m)	730
Height (-H- m)	820
Weight (kg)	350
DIMENSIONS (PACKED)*	
Length (-L- m)	1630
Width (-W- m)	831
Height (-H- m)	990
Weight (kg)	400
Tank Capacity	38

ENGINE	
Brand	Bundu Power
Model	KM376AG
Type	Three cylinder: four stroke, water cooled
Starting System	12 Volt Electric Starter
Auto-Decompression	Yes
Cubic Capacity (L)	1.048
Compression Ratio	21.5:1
Rated Power (kW/rpm)	16.5 / 3000
Fuel Type	Diesel
Lube Oil	L-ECD grade or 15W40
Low Pressure Alert	Yes
Low Fuel Cut Out	Yes

CONTROL PANEL	
Model	GU611
Type	Digital
Analogue Inputs	2
Mains Phase Voltage	Yes
Mains Line Voltage	Yes

ALTERNATOR	
Model	KTS19
Rated Current (A)	62.6
Pole Number	2
Excitation Mode	Brushless / Self Excitation



ADDITIONAL	
Running Time per Tank (Hr)	8.0 @ full load
Structure Type	Silent (Not Weatherproof)
Noise Level (dBA @ 7m)	70 - 74
Auto Voltage Regulator (AVR)	Constant voltage AVR
ISO9001 & CE Certified	Yes

* Figures are subject to change without prior notice.

** The mentioned power values are according to ISO8528-1 Standards