

GENERAL DATA	
Model	IG6000
Continuous / Prime power (P.R.P)	5.5
Stand-by power (L.T.P)	6.0
Amps (A)	24
Power Factor / Cos ( $\phi$ )	0.8
Frequency	50
Voltage	230
No. phases	Single Phase
Engine Speed	3600

DIMENSIONS (UNPACKED)*	
Length (-L- m)	700
Width (-W- m)	500
Height (-H- m)	640
Weight (kg)	95
DIMENSIONS (PACKED)*	
Length (-L- m)	720
Width (-W- m)	530
Height (-H- m)	670
Weight (kg)	115
Tank Capacity	22

ENGINE	
Brand	Bundu Power
Model	KG390Gi
Type	Single Cylinder: four stroke, vertical, air cooled
Starting System	12 Volt Electric Starter
Auto-Decompression	Yes
Cubic Capacity (L)	0.389
Compression Ratio	8.5:1
Rated Power (kW/rpm)	7.7 / 3600
Fuel Type	Unleaded Petrol
Lube Oil	SAE10W30
Low Pressure Alert	Yes
Low Fuel Cut Out	Yes

CONTROL PANEL	
Model	GU611
Type	Digital
Analogue Inputs	2
Mains Phase Voltage	Yes
Mains Line Voltage	Yes

ALTERNATOR	
Model	MJB225MA4
Rated Current (A)	24
Pole Number	2
Excitation Mode	Brushless / Self Excitation



ADDITIONAL	
Running Time per Tank (Hr)	7.5 @ full load
Structure Type	Silent (Not Weatherproof)
Noise Level (dBA @ 7m)	70 - 74
Auto Voltage Regulator (AVR)	Constant voltage AVR
ISO9001 & CE Certified	Yes

\* Figures are subject to change without prior notice.

\*\* The mentioned power values are according to ISO8528-1 Standards