

3.8 KVA PETROL GENERATOR

FEATURES & BENEFITS

- Maximum 4.2 kVA, 230V, Smart Throttled RPM
- Inverter Type (Automatic Voltage Regulator)
- Electric & Recoil
- 8 Litre Fuel Tank, 5 Hours @ 75% load
- Silent "Suitcase" Type Version (± 72 dBa)
- Single Cylinder, Forced Air-Cooling, 4-stroke
- Single Phase Output
- 3-in-1 Display Meter Digital
- DC Output for battery Charging
- Colours May Vary



Colours may vary.

GENERAL DATA

Model:	BP4500ISE-PRO
Prime Power (P.R.P):	3.8 kVA
Stand-by Power (L.T.P):	4.2 kVA
Amps:	18.2 A
Power Factor / COS:	1
Frequency:	50 Hz
Voltage:	230 V
Phases:	Single Phase
Engine Speed:	Smart Throttled RPM
Length:	575 mm
Width:	340 mm
Height:	530 mm
Weight:	31.5 kg's
Tank Capacity:	8 l

ADDITIONAL

Running Time:	5 Hours @ 75% load
Structure Type:	Silent "Suitcase" Type
Noise Level (7m):	72 dBA
Auto Voltage Regulator:	Inverter Type
ISO9001 Certified:	Yes
CE Certified:	Yes
Fuel Cons. @ 100% Load:	2.0
Fuel Cons. @ 75% Load:	1.5
Fuel Cons. @ 50% Load:	1.0

ENGINE DATA

Brand:	Genkins
Model:	LT175VI
Type:	Single Cylinder, Forced Air-Cooling, 4-stroke
Starting System:	Electric & Recoil
Auto-Decompression:	Yes
Cubic Capacity (l):	0.175
Compression Ratio:	8.8:1
Rated Power (kW/RPM):	4.2kW
Fuel Type:	Petrol
Lube Oil:	10W-30 / SAE30
Low Pressure Alert:	N/A
Low Fuel Cut Out:	N/A

CONTROL PANEL

Model:	3-in-1 Display Meter
Type:	Digital
Analogue Inputs:	N/A
Mains Phase Voltage:	No
Mains Line Voltage:	No

ALTERNATOR

Model:	
Pole Number:	N/A
Excitation Mode:	

- * Specs subject to change without prior notice.
- * Measurements based on ISO8528-1 Standards
- * All rating at Sea Level, 25°C Ambient Temp.