

## 2050 KVA DIESEL GENERATOR

### FEATURES & BENEFITS

- Maximum 2250 kVA, 380V, 1500 RPM
- Constant voltage AVR (Automatic Voltage Regulator)
- 24 Volt Electric Starter
- External Litre Fuel Tank
- Container Version ( $\pm 80$ dBa)
- V12, 4 stroke, water-cooled, Turbo charged with aftercooler
- Three Phase Output
- DeepSea DSE8610 Digital Control Panel
- Low oil pressure system
- Low water cut out engine protection



**MOTEURS**  
**Baudouin**

GENERAL DATA	
<b>Model:</b>	BPD2050-TP
<b>Prime Power (P.R.P):</b>	2050 kVA
<b>Stand-by Power (L.T.P):</b>	2250 kVA
<b>Amps:</b>	3410 A
<b>Power Factor / COS:</b>	0.8
<b>Frequency:</b>	50 Hz
<b>Voltage:</b>	380 V
<b>Phases:</b>	Three Phase
<b>Engine Speed:</b>	1500 RPM
<b>Length:</b>	12192 mm
<b>Width:</b>	2438 mm
<b>Height:</b>	2896 mm
<b>Weight:</b>	23000 kg's
<b>Tank Capacity:</b>	External I

ADDITIONAL	
<b>Running Time:</b>	
<b>Structure Type:</b>	Container
<b>Noise Level (7m):</b>	80 dBA
<b>Auto Voltage Regulator:</b>	Constant voltage AVR
<b>ISO9001 Certified:</b>	Yes
<b>CE Certified:</b>	Yes
<b>Fuel Cons. @ 100% Load:</b>	414
<b>Fuel Cons. @ 75% Load:</b>	322
<b>Fuel Cons. @ 50% Load:</b>	207

ENGINE DATA	
<b>Brand:</b>	BAUDOIN
<b>Model:</b>	12M26G1100/5 x 2
<b>Type:</b>	V12, 4 stroke, water-cooled, Turbo charged with aftercooler
<b>Starting System:</b>	24 Volt Electric Starter
<b>Auto-Decompression:</b>	Yes
<b>Cubic Capacity (l):</b>	31.8
<b>Compression Ratio:</b>	15.7:1
<b>Rated Power (kW/RPM):</b>	1778 / 1500 (889 x 2)
<b>Fuel Type:</b>	Diesel
<b>Lube Oil:</b>	15W40
<b>Low Pressure Alert:</b>	Yes
<b>Low Fuel Cut Out:</b>	Yes


CONTROL PANEL	
<b>Model:</b>	DeepSea DSE8610
<b>Type:</b>	Digital Control Panel
<b>Analogue Inputs:</b>	2
<b>Mains Phase Voltage:</b>	Yes
<b>Mains Line Voltage:</b>	Yes

ALTERNATOR	
<b>Model:</b>	DPC404G x 2
<b>Pole Number:</b>	4
<b>Excitation Mode:</b>	Self Excitation

\* Specs subject to change without prior notice.

\* Measurements based on ISO8528-1 Standards

\* All rating at Sea Level. 25°C Ambient Temp.


	Model : <b>12M26G1100/5</b>	Date : 14/01/19
	<b>PowerKit Engine Datasheet</b>	Page : 1 / 4

## Ratings

RPM	Gross Engine Output	
	PRP kWm	ESP kWm
1500	889	973

## Basic data

Engine model	.....	12M26G1100/5
N° of Cylinders / Valves	.....	12 / 48
Cylinders arrangement	.....	At Vee
Bore x Stroke (mm)	.....	150 x 150
Displacement (L)	.....	31.8
Thermodynamic Cycle	.....	Diesel 4 stroke
Cooling System	.....	Liquid (water + 50% antifreeze)
Injection System	.....	Direct
Fuel System	.....	Mechanical Pump
Aspiration	.....	Turbocharged and Aftercooled
Compression ratio	.....	15.7 : 1
Flywheel housing	.....	SAE 0
Flywheel	.....	18"
N° of teeth on flywheel ring gear	.....	178
Inertia of flywheel (kg/m <sup>2</sup> )	.....	6.95
Inertia of crankshaft (kg/m <sup>2</sup> )	.....	1.47
Emission standard	.....	N/A
Overall Dimensions with radiator (Length x Width x Height) (mm)	.....	2873 x 1659 x 1793
Engine dry weight (kg)	.....	3310
Engine wet weight (includes oil, coolant) (kg)	.....	3570

	Model : <b>12M26G1100/5</b>	Date : 14/01/19
	<b>PowerKit Engine Datasheet</b>	Page : 2 / 4

## Air intake system

Air intake temperature rise (°C) .....	≤ 5
Air intake restriction clean filter (mBar) .....	≤ 30
Air intake restriction dirty filter (mBar) .....	≤ 65
Recommended air flow @ PRP (m <sup>3</sup> /min) .....	63,5
Recommended air flow @ ESP (m <sup>3</sup> /min) .....	68,9
Min. diameter of intake pipe (mm) .....	140

## Intercooling system


Intercooler heat dissipating capacity @ PRP (kJ/s) .....	159.8
Intercooler heat dissipating capacity @ ESP (kJ/s) .....	176.1
Max. intake temperature @ 25°C ambient temperature (°C) .....	60
Max. difference between intake temperature and ambient temperature (°C) .....	≤ 21
Max. intake pressure drop of intercooler (mBar) .....	150

## Cooling system with Made in EU radiator

System designed for ambient temperature up to (°C) .....	50
Radiator type .....	Mechanical
Fan type .....	Belt driven pusher
Min. inside diameter of coolant outlet pipe (mm) .....	84
Coolant capacity of radiator and pipes (L) .....	65
Coolant alarm (shutdown) temperature (°C) .....	103
Thermostat opening temperature / full open temperature (°C) .....	77 / 87
Min. pressure in cooling system (Bar) .....	0.5
Coolant capacity of the engine (L) .....	83
Cooling fan airflow (m <sup>3</sup> /min) .....	840
Max additional restriction - Duct allowance (Pa) .....	140

## Exhaust system

Max. exhaust back pressure (mBar) .....	75
Max. exhaust temperature before turbocharger (°C) .....	≤ 750
Max. exhaust temperature after turbocharger (°C) .....	≤ 550
Exhaust flow @ PRP (m <sup>3</sup> /min) .....	216,2
Exhaust flow @ ESP (m <sup>3</sup> /min) .....	253
Min. diameter of exhaust pipe (mm) .....	200
Max. bending moment of exhaust gas exit flange (Nm) .....	10

	Model : <b>12M26G1100/5</b>	Date : 14/01/19
	<b>PowerKit Engine Datasheet</b>	Page : 3 / 4

## Lubrication system

Oil capacity Low / High (L) .....	78 / 109
Oil pressure in normal condition idle speed (Bar) .....	≥ 2
Oil pressure in normal condition at 1500 Rpm @ PRP (Bar) .....	4 - 6
Lowest oil pressure alarm (shutdown) (Bar) .....	2
Max. oil temperature (°C) .....	105
Oil flow (L/min) .....	≥ 350
Oil fuel consumption ratio based on engine fuel consumption data .....	≤ 0.3 %
Total system capacity (including filters) (L) .....	114

## Noise


Diesel engine noise (Acoustic power level) (dB(A)) .....	121.4
--	-------

## Fuel system

Governor .....	Electronic
Max. restriction at fuel pump inlet (Bar) .....	0.5
Max. fuel return restriction (Bar) .....	0.5
Max. fuel inlet temperature (°C) .....	70
Fuel supply flow (L/hr) .....	595
Min. pressure of fuel pump (Bar) .....	1.3
Min. diameter of inlet pipe (mm) .....	14
Min. diameter of return pipe (mm) .....	14

## Electrical system

Electrical system voltage (negative to ground) (Vdc) .....	24
Starter power (kW) .....	10
Battery charger current (A) .....	55
Max. electric resistance of starting circuit (Ω) .....	0.008
Min. sectional area of wire (mm <sup>2</sup> ) .....	95
Min. cold start temperature without auxiliary starting device (°C) .....	0
Min. cold start temperature with auxiliary starting device (°C) .....	- 10

	Model : <b>12M26G1100/5</b>	Date : 14/01/19
	<b>PowerKit Engine Datasheet</b>	Page : 4 / 4

### Heat balance test data (with ambient temperature 28 °C)

Total heat dissipation @ ESP (kJ/s) .....1298.7

### Performance data

Mean Piston Speed (m/s) .....7.5

BMEP (Bar) .....24.48

Fan absorbed power (kW) .....26,5

### Fuel consumption

Rating	gr/kWh	L/hr
100% ESP	196.9	227.4
100% PRP	195.7	205.2
75% PRP	195.7	154
50% PRP	201.4	105.7
25% PRP	220.7	57.8
Fuel consumption tolerance + 3 %		

### Ratings definitions

#### Emergency Standby Power (ESP)

Emergency Standby Power is the maximum power available for a varying load for the duration of a main power network failure. The average load factor over 24 hours of operation should not exceed 70% of the engine's ESP power rating. Typical operational hours of the engine is 200 hours per year, with a maximum usage of 500 hours per year. This includes an annual maximum of 25 hours per year at the ESP power rating. No overload capability is allowed. The engine is not to be used for sustained utility paralleling applications.

#### Prime Power (PRP)

Prime Power is the maximum power available for unlimited hours of usage in a variable load application. The average load factor should not exceed 70% of the engine's PRP power rating during any 24 hour period. An overload capability of 10% is available, however, this is limited to 1 hour within every 12 hour period.

- 1) All ratings are based on operating conditions under ISO 8528-1, ISO 3046, DIN6271. Performance tolerance of ±5%.
- 2) Test conditions : 100 kPa, 25°C air inlet temperature, relative humidity of 30%, with fuel density 0.84 kg/L. Derating may be required for conditions outside these; please contact the factory for details.
- 3) Power output curves are based on the engine operating with fuel system, water pump and lubricating oil pump; not included are battery charging alternator, fan and optional equipment.