

## 327 KVA DIESEL GENERATOR

### FEATURES & BENEFITS

- Maximum 360 kVA, 380V, 1500RPM
- Constant voltage AVR (Automatic Voltage Regulator)
- 
- 470 Litre Fuel Tank, 8 Hours @ 75% load
- Silent Version ( $\pm 78$ dBa)
- 6 cylinder inline, Turbocharged & charge air cooled
- Three Phase Output
- DeepSea DSE6120 Digital Control Panel
- Low oil pressure system
- Low water cut out engine protection



GENERAL DATA	
<b>Model:</b>	C330A
<b>Prime Power (P.R.P):</b>	327 kVA
<b>Stand-by Power (L.T.P):</b>	360 kVA
<b>Amps:</b>	546 A
<b>Power Factor / COS:</b>	0.8
<b>Frequency:</b>	50 Hz
<b>Voltage:</b>	380 V
<b>Phases:</b>	Three Phase
<b>Engine Speed:</b>	1500 RPM
<b>Length:</b>	3963 mm
<b>Width:</b>	1356 mm
<b>Height:</b>	2171 mm
<b>Weight:</b>	3470 kg's
<b>Tank Capacity:</b>	470 l

ADDITIONAL	
<b>Running Time:</b>	
<b>Structure Type:</b>	Silent
<b>Noise Level (7m):</b>	78 dBA
<b>Auto Voltage Regulator:</b>	Constant voltage AVR
<b>ISO9001 Certified:</b>	Yes
<b>CE Certified:</b>	Yes
<b>Fuel Cons. @ 100% Load:</b>	70
<b>Fuel Cons. @ 75% Load:</b>	55
<b>Fuel Cons. @ 50% Load:</b>	37

ENGINE DATA	
<b>Brand:</b>	Cummins
<b>Model:</b>	6LTAA9.5-G1
<b>Type:</b>	6 cylinder inline, Turbocharged & charge air cooled
<b>Starting System:</b>	
<b>Auto-Decompression:</b>	Yes
<b>Cubic Capacity (l):</b>	9.5
<b>Compression Ratio:</b>	16.6:1
<b>Rated Power (kW/RPM):</b>	320 / 1500
<b>Fuel Type:</b>	Diesel
<b>Lube Oil:</b>	15W40
<b>Low Pressure Alert:</b>	Yes
<b>Low Fuel Cut Out:</b>	Yes

CONTROL PANEL	
<b>Model:</b>	DeepSea DSE6120
<b>Type:</b>	Digital Control Panel
<b>Analogue Inputs:</b>	2
<b>Mains Phase Voltage:</b>	Yes
<b>Mains Line Voltage:</b>	Yes

ALTERNATOR	
<b>Model:</b>	AKS-360
<b>Pole Number:</b>	4
<b>Excitation Mode:</b>	Self Excitation

\* Specs subject to change without prior notice.

\* Measurements based on ISO8528-1 Standards

\* All rating at Sea Level, 25°C Ambient Temp.