

## 750 KVA DIESEL GENERATOR

### FEATURES & BENEFITS

- Maximum 825 kVA, 380V, 1500 RPM
- Constant voltage AVR (Automatic Voltage Regulator)
- 24 Volt Electric Starter
- 1000 Litre Fuel Tank, 8 Hours @ 75% load
- Silent Version ( $\pm 78$ dBa)
- 12-Cylinder, V-Type, Turbocharged intercooled
- Three Phase Output
- DeepSea DSE7320 Digital Control Panel
- Low oil pressure system
- Low water cut out engine protection



GENERAL DATA	
<b>Model:</b>	DS740A
<b>Prime Power (P.R.P):</b>	750 kVA
<b>Stand-by Power (L.T.P):</b>	825 kVA
<b>Amps:</b>	1250 A
<b>Power Factor / COS:</b>	0.8
<b>Frequency:</b>	50 Hz
<b>Voltage:</b>	380 V
<b>Phases:</b>	Three Phase
<b>Engine Speed:</b>	1500 RPM
<b>Length:</b>	5313 mm
<b>Width:</b>	1606 mm
<b>Height:</b>	2658 mm
<b>Weight:</b>	5780 kg's
<b>Tank Capacity:</b>	1000 l

ADDITIONAL	
<b>Running Time:</b>	8 Hours @ 75% load
<b>Structure Type:</b>	Silent
<b>Noise Level (7m):</b>	78 dBA
<b>Auto Voltage Regulator:</b>	Constant voltage AVR
<b>ISO9001 Certified:</b>	Yes
<b>CE Certified:</b>	Yes
<b>Fuel Cons. @ 100% Load:</b>	161
<b>Fuel Cons. @ 75% Load:</b>	125
<b>Fuel Cons. @ 50% Load:</b>	85

ENGINE DATA	
<b>Brand:</b>	DOOSAN
<b>Model:</b>	DP222LC
<b>Type:</b>	12-Cylinder, V-Type, Turbocharged intercooled
<b>Starting System:</b>	24 Volt Electric Starter
<b>Auto-Decompression:</b>	Yes
<b>Cubic Capacity (l):</b>	21.927
<b>Compression Ratio:</b>	15:1
<b>Rated Power (kW/RPM):</b>	723 / 1500
<b>Fuel Type:</b>	Diesel
<b>Lube Oil:</b>	15W40
<b>Low Pressure Alert:</b>	Yes
<b>Low Fuel Cut Out:</b>	Yes

CONTROL PANEL	
<b>Model:</b>	DeepSea DSE7320
<b>Type:</b>	Digital Control Panel
<b>Analogue Inputs:</b>	2
<b>Mains Phase Voltage:</b>	Yes
<b>Mains Line Voltage:</b>	Yes

ALTERNATOR	
<b>Model:</b>	DPC314F
<b>Pole Number:</b>	4
<b>Excitation Mode:</b>	Self Excitation

\* Specs subject to change without prior notice.

\* Measurements based on ISO8528-1 Standards

\* All rating at Sea Level, 25°C Ambient Temp.